

PULLCAP FUSE-HOLDERS FOR FUSE-LINKS


TYPE LPC

240 & 415 Volt Fuse-holders for Fuse-Links to IEC 60269-1,-3/BS 88-1,-3 and BS 1361

Rated Voltages 240 & 415V a.c. Breaking Capacities 16.5 & 80kA a.c.



Also available: DIN-Rail Adaptor for 32A Base – Ref. LPC 32 DA.A range of assembled PULLCAP Fuse-Holders.



PRODUCT DETAILS

SPECIFICATIONS

Component	List Reference	Current Rating (A)	Lawson Fuse Type	Solid Link	Colour
Carrier	LPC 5 CA WH	5	LA	-	White
	LPC 5 CA BK	5	LA	-	Black
	LPC 20 CA BL	20	LC	SLPC 20	Blue
	LPC 20 CA GN	20	LC	SLPC 20	Green
	LPC 32 CA RD	32	LD	SLPC 32	Red
	LPC 32 CA BK	32	MD	SLPC 32	Black
	LPC 63 CA BK	63	ME	-	Black
Cover Plate	LPC 5 CP WH	5	LA	-	White
	LPC 5 CP BK	5	LA	-	Black
	LPC 20 CP BL	20	LC	SLPC 20	Blue
	LPC 20 CP GN	20	LC	SLPC 20	Green
	LPC 32 CP BK	32	LD	SLPC 32	Red
	LPC 32 CP BK	32	MD	SLPC 32	Black
	LPC 00 CP BK	0	Blank	-	Black
	LPC 63 CP BC	63	ME	-	Black
Base	LPC 32 FC/FC	32			
	LPC 32 FC/BBC				
	LPC 32 FC/BC				
	LPC 32 FC/BC				
	LPC 32 FCL/FCL				
	LPC 32 FCL/FCL	63			
	LPC 63 FC/FC				
	LPC 63 FC/BBC				
	LPC 63 FC/BC				
	LPC 63 BC/BC				
LPC 63 FCL/FCL					

