

MINIATURE FUSE-LINKS

TYPE MIN

230/240 Volt Miniature Fuse-Links to IEC 60127

Rated Voltage 250V a.c. Breaking Capacities – Various



Lawson type MIN Fuse-Links are available to meet a wide variety of applications.

Miniature and other small dimensioned Fuse-Links are grouped into several different application categories and comply with different specifications.

Many different types are available with current ratings from 10mA to 30A



PRODUCT DETAILS

CURRENT RATINGS AND PRINCIPAL DIMENSIONS - 5 X 20

Type Reference	Dimensions (mm)	Operating Characteristics	Body Material	Rating		Fuse Holder Type
				mA	Amps	
PDC	5 X 20	Fast	Glass	32,40,50,63,80,100,125,160	1, 1.25,1.6,2.2,2.5,3.15,4,5	KP
PCC				200,315,400,500,630,800	6.3,8,10,15	
PDC-S		Slow	Glass	32,40,50,63,80,100,125,160	1, 1.25,1.6,2.2,2.5,3.15,4,5	
PCC-S				200,315,400,500,630,800	6.3,8,10	
PCC-UR		Ultra Fast	Ceramic	125,160,200,250,315	1, 1.25,1.6,2.2,2.5,3.15,4,5	
				400,500,630,800	6.3,8,10	
				1.6,2,3,15,4,5,8,10		

CURRENT RATINGS AND PRINCIPAL DIMENSIONS - 6.3 X 32

Type Reference	Dimensions (mm)	Operating Characteristics	Body Material	Rating		Fuse Holder Type
				mA	Amps	
KDC	6.3 x 32	Fast	Glass	10,32,40,63,100,125,150,175,187	1, 1.25,1.5,1.6,2.2,2.5,3,4,5,6,7,8,10	K
KCC				125,250,375,500,750	1,2,3,4,5,6,7,8,10,12,15,20,25,30	
KCD-S		Slow	Glass	10,32,40,63,100,125,150,175,187, 200	5,6,7,8,20,25,30	
KCC-S				10,32,63,100,125,150,175,187, 200	1, 1.25,1.5,1.6,2.2,2.5,3,4,5,6,7,8,10,12,15,20,25,30	
KCC-UR		Ultra Fast	Ceramic	250,300,375,400,500,600,700,750, 800	1,1.25,2,3,4,5,6,7,8,10,12,15,20,25,30	

CURRENT RATINGS AND PRINCIPAL DIMENSIONS - 5 x 25

Type Reference	Dimensions (mm)	Operating Characteristics	Body Material	Rating	
				mA	Amps
TDC	5 x 25	Fast	Glass	80,100,125,160,200	1, 1.25,1.6,2.2,2.5,3.15,4,5
TCC				250,315,400,500,630, 800	6.3,8,10
TDC-M			Ceramic C/W Indicator	80,100,125,160,200	1, 1.25,1.6,2.2,2.5,3.15,4,5
TCC-M				250,315,400,500,630, 800	6.3,8,10
			Ceramic C/W Indicator	80,100,125,160,200	1, 1.25,1.6,2.2,2.5,3.15,4,5
				250,315,400,500,630, 800	6.3,8,10